

# APPARATUS FOR AUTOMATICALLY PERFORMING A BIOTECHNOLOGICAL PROCESS AT DIFFERENT DESIRED TEMPERATURES

Publication number: JP5503466T

Publication date: 1993-06-10

Inventor:

Applicant:

Classification:

- international: **B01L7/02; B01L7/00; B01L11/02; C12M1/36; G01N35/00; G05D23/00; G05D23/19; H05B6/68; H05B6/80; B01L7/00; B01L11/00; C12M1/36; G01N35/00; G05D23/00; G05D23/19; H05B6/68; H05B6/80; (IPC1-7): B01L7/02; B01L11/02; C12M1/36; G05D23/00; H05B6/80**

- European: **B01L7/00D; G05D23/19E; H05B6/68M4**

Application number: JP19910505871 19910228

Priority number(s): NL19900000481 19900228

Also published as:


WO9112888 (A)  
EP0539375 (A1)  
US5302347 (A1)  
NL9000481 (A)  
EP0539375 (A0)

Report a data error he

Abstract not available for JP5503466T

Abstract of corresponding document: **WO9112888**

An apparatus for automatically performing a biotechnological process at different desired temperatures comprises a reactor space (1) with a water bath (2) in which a plurality of sample containers (5) with samples to be examined can be placed. The desired temperatures and periods during which each adjusted temperature should be maintained, are adjustable by adjustment means, wherein a temperature sensor (13) for measuring the temperature of the water bath is provided and a control unit (11) controls the temperature of the water bath in dependence on the measured temperature and time. At least one magnetron tube (12) is provided in the reactor space for heating the water bath and the sample containers placed in the same. The water bath is connectable to a water conduit through a water supply conduit (6) wherein the control unit (11) controls the magnetron tube (12) and the valves (7, 9) in dependence on the desired temperature and time.



Data supplied from the **esp@cenet** database - Worldwide